


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 7 : B23P 19/08, F16J 15/06, 15/02</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/47364 (43) International Publication Date: 17 August 2000 (17.08.00)</p>
<p>(21) International Application Number: PCT/CA00/00128 (22) International Filing Date: 10 February 2000 (10.02.00) (30) Priority Data: 60/119,390 10 February 1999 (10.02.99) US (71) Applicant (for all designated States except US): TESMA INTERNATIONAL INC. [CA/CA]; 99 Ortona Court, Concord, Ontario L4K 3M3 (CA). (72) Inventors; and (75) Inventors/Applicants (for US only): <u>FOLINO, Salvatore, J.</u> 180 [CA/CA]; 64 Center Avenue, Willowdale, Ontario M2M 2L5 (CA). <u>VERT, Peter, J.</u> [CA/CA]; 167 Silver Arrow Crescent, Maple, Ontario L6A 1K2 (CA). <u>BAUMAN, Cecil</u> [CA/CA]; 26 Broadway Street, Hawkesville, Ontario M0B 1X0 (CA). <u>CAX</u> (74) Agent: IMAI, Jeffrey, T.; Magna International Inc., 337 Magna Drive, Aurora, Ontario L4G 7K1 (CA).</p>		<p>(81) Designated States: CA, MX, US. Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: GASKET INSTALLATION APPARATUS</p>		
		
<p>(57) Abstract</p> <p>An apparatus (50) and method for inserting a gasket (32) into a channel (28) of a mating part (20). The apparatus includes a gasket carrier (66) having a convexly curved surface with a groove (78) therein for receiving a base (34) of the gasket. The groove registers with the channel to feed the gasket into the channel in response to relative rocking movement between the part and the surface. According to the method, a gasket is placed in the groove and the gasket carrier is juxtaposed with the part to align the gasket with the channel. The part and the gasket carrier are moved toward each other for a portion of the gasket to enter the channel. A relative rocking movement is caused between the part and the gasket carrier to transfer the remainder of the gasket to the channel.</p>		